

xDSL Splitter

Outline

Splitters developed to meet the needs of the recent mainstream xDSL market.

Features

PSR-1330

- Compact and lightweight.
- Meets ITU-T G.992.5 Annex E Type-4 Type for JAPAN market.

PSR-1401

- Compact and lightweight.
 - Meets ITU-T G.993.1 (G.vdsl.f) Annex F requirements.
- PSC-8000
- Compact and meets high density mounting.
 - Meets ETSI TS 101 952-1-1 OPTION-A requirements.
 - In hope, please ask offer of Splitter boards to us.



PSR-1330



PSR-1401



PSC-8000

Applications

- PSR-1330 : Telephone, leased lines.
- PSR-1401 : Telephone, leased ISDN lines.
- PSC-8000 : Telephone, leased lines in Europe.

Specifications

Model	Suiting area	Insertion Loss (dB)	Frequency characteristics (dB)	Return Loss (dB)	Attenuation (dB)	Special matter
PSR-1330	JAPAN	> 1.0 (at 1.0kHz)	$\leq \pm 1.0$ (200Hz to 3.4kHz) $\leq \pm 1.5$ (3.4kHz to 4.0kHz)	≥ 11.0 (200Hz to 1.5kHz) ≥ 10.0 (1.5kHz to 2.0kHz) ≥ 9.0 (2.0kHz to 3.4kHz)	$\leq \pm 70.0$ (25.0kHz to 300kHz) $\leq \pm 55.0$ (300kHz to 3.75MHz)	
		POTS Band ≤ 1.0 (at 1.0kHz)		POTS Band ≥ 11.0 (200Hz to 1.5kHz) ≥ 10.0 (1.5kHz to 2.0kHz) ≥ 9.0 (2.0kHz to 3.4kHz)		
PSR-1401	JAPAN		POTS Band $\leq \pm 1.0$ (200Hz to 3.4kHz) $\leq \pm 1.5$ (3.4kHz to 4.0kHz)	ISDN Band ≥ 7.0 (4.0kHz to 10.0kHz) ≥ 15.0 (10.0kHz to 160kHz) ≥ 12.2 (160kHz to 220kHz)	≥ 42.14 (0.64MHz to 0.932MHz) ≥ 65.0 (0.932MHz to 6.0MHz) ≥ 55.0 (12MHz to 30.0MHz)	
		ISDN Band ≤ 1.0 (4.0kHz to 160kHz) ≤ 4.0 (at 320kHz)		VDSL Band ≥ 6.0 (0.64MHz to 1.28MHz) ≥ 12.0 (0.64MHz to 30.0MHz)		
PSC-8000	EUROPE	> 1.0 (at 1.0kHz) Load impedance: Zr, ZsL	> 1.0 (200Hz-4.0kHz, 600ohm, Zr)	> 12.0 (300Hz to 3.4kHz) > 8.0 (3.4kHz to 4.0kHz)	> 55.0 (32.0kHz to 30.0MHz)	We can offer Splitter board Designed to meet VDSL2



- All specifications in this catalog and production status of products are subject to change without notice. Prior to the purchase, please contact NEC Tokin for updated product data.
- Please request for a specification sheet for detailed product data prior to the purchase.
- Before using the product in this catalog, please read "Precautions" and other safety precautions listed in the printed version catalog.

NEC TOKIN Corporation

Precautions



- The names of the products and the specifications in this catalog are subject to change without notice for the sake of improvement. The manufacturer also reserves the right to discontinue any of these products. At the time of delivery, please ask for specifications sheets to check the contents before use.
- Descriptions in this catalog regarding product characteristics and quality are based solely on discrete components. When using these components, be sure to check the specifications with the component in question mounted on the products.
- The manufacturer's warranty will not cover any disadvantage or damage caused by improper use of the products that deviates from the characteristics, specifications, or conditions for use described in this catalog.
- The products in this catalog are intended for use in ordinary electronic products. If any of these products are to be used in special applications requiring extremely high reliability, where product defects might pose a safety risk, please consult your NEC TOKIN sales representatives.
- Though the manufacturer has taken all possible precautions to ensure the quality and reliability of its products, improper use of products may result in bodily injury, fire, or similar accident. If you have any questions regarding the use of the products in question, please consult your NEC TOKIN sales representatives.
- Please be advised that the manufacturer accepts no responsibility for any infringement by users of the manufacturer's products on third party patents or industrial copyrights. The manufacturer is responsible only when such infractions are attributable to the structural design of the product and its manufacturing process.
- Export Control
For customers outside Japan
NEC-TOKIN products should not be used or sold for use in the development, production, stockpiling or utilization of any conventional weapons or mass-destructive weapons (nuclear weapons, chemical or biological weapons, or missiles), or any other weapons.
For customers in Japan
For products which are controlled items subject to the 'Foreign Exchange and Foreign Trade Law' of Japan, the export license specified by the law is required for export.
- This catalog is current as of September 2006.

For inquiry, Please call Sales Promotion Department (Japan)

Phone: 81-3-3515-9220 Fax: 81-3-3515-9221

©2006 NEC TOKIN Corporation

2nd Sales Unit Global Sales Division Phone:81-3-3515-9220	NEC TOKIN Singapore Pte.Ltd. Phone:65-6223-7076
Seoul Branch Phone:82-2-551-3651	Malaysia Branch Phone:60-3-6201-0702
NEC TOKIN America Inc. Phone:1-510-324-4110	NEC TOKIN Thailand Co., Ltd. Phone:66-2-260-7017
Chicago Branch (Northeast Sales office) Phone:1-847-981-5047	NEC TOKIN Taiwan Co., Ltd. Phone:886-2-2521-3998
Austin Branch (Southeast Sales office) Phone:1-512-219-4040	NEC TOKIN Europe GmbH Phone:49-2131-1866-0
NEC TOKIN Hong Kong Ltd. Phone:852-2730-0028	Munich Office Phone:49-89-944-197-0
NEC TOKIN Shanghai Co., Ltd. Phone:86-21-6473-4437	France Branch Phone:33-1-39-452011
NEC TOKIN Shenzhen Co., Ltd. Phone:86-755-8246-5011	Sweden Representative Office Phone:46-8-712-91-05

<http://www.nec-tokin.com>

0742BDXS07VOL02E September 00, 2006 H00P3
Printed in Japan



- All specifications in this catalog and production status of products are subject to change without notice. Prior to the purchase, please contact NEC Tokin for updated product data.
- Please request for a specification sheet for detailed product data prior to the purchase.
- Before using the product in this catalog, please read "Precautions" and other safety precautions listed in the printed version catalog.